



CUREAID AC

Acrylic Curing Agent

DESCRIPTION

CUREAID AC is an acrylic-based curing agent which will penetrate into the matrix within the surface of cementitious repair mortars and coatings to form a sealed surface which conforms to ASTM C309. Once cured it retains its mechanical properties and provides excellent resistance to weathering.

USES

CUREAID AC is designed for use in conjunction with PREMCRETE CONCRETE REPAIR and protection system. It does not de-grade once applied, making it particularly suitable for external application where increased mechanical properties are required.

PROCEDURE

Surface Preparation: Where CUREAID AC is to be applied to a cementitious repair or coating product then application should begin once the mortar or coating has been levelled to the correct finish. If CUREAID AC is to be applied to a standard concrete, then allow for the bleed water to disperse before application.

Application: CUREAID AC should be spray applied to the surface of the recently placed mortar or screed immediately once finishing has completed. CUREAID AC should be spray applied evenly to the surface at a rate of approximately 5 M2 per litre. In exceptional circumstances here there is strong direct sunlight or wind, then a second coat should be applied at the same rate once the first coat has dried.

Curing: CUREAID AC should be allowed to cure for a minimum of 3 days before overcoating with any subsequent paints or coatings.

Equipment Cleaning: Tools and equipment should be cleaned immediately using water.

Property	Value
Appearance	White
Specific Gravity	1.04 @ 20°C
Flash Point	N/A
Viscosity	60 cps

PACKAGING & COVERAGE

Pack Size: CUREAID AC is supplied as a 5ltr pack.

Coverage: CUREAID AC should be applied at approximately 0.2 ltrs per M2 per coat.

STORAGE & SHELF LIFE

Store in cool, dry, frost-free conditions.

HEALTH & SAFETY

See separate material safety datasheet



Premcrete Ltd | Reg no. 08079452 VAT no. 194306207

Structural Waterproofing | Gas Protection
| Concrete Repair Technical Grouts | Joint
Sealants | Protective Coatings | Admixtures

www.premcrete.com | 02380 276166 |
sales@premcrete.com | 44 Macadam Way,
West Portway, Andover, Hampshire, SP10
3XW

The information provided in this data sheet is intended for general guidance only and is given in good faith based on Premcrete Ltd current knowledge and experience. No warranty in respect of fitness for a purpose, or any other liability whatsoever can be inferred from the information contained within this datasheet. Users should determine the suitability of the materials for their particular application and should always refer to the most recent issue of the product data sheet for the product concerned. All materials are supplied in accordance with Premcrete Ltd Sales Terms & Conditions (available upon request and on Company Website).