



# Hydroflow Corner Tape

## BUTYL JOINTING TAPE/ROPE

### DESCRIPTION

HYDROFLOW CORNER TAPE is a high performance pressure sensitive butyl sealant manufactured from the latest rubber polymer technology, available in black. The strip sealant is laminated to a clear tear resistant film.

### USES

Hydroflow Butyl Sealant is used to seal Hydroflow HP cavity drainage membrane sheets to produce a water and vapour tight seal.

### ADVANTAGES

- Highly conformable to most substrates
- Excellent adhesion
- Good chemical and UV resistance
- Easy release liner which aids application
- Good movement accommodation

Property	Value
Density	1.3Kg <sup>3</sup>
Service Temperature	-40°C to +90°C
Application Temperature	+5C
Peel Adhesion	30N/in
Loop Tack	35N/in <sup>2</sup>



Premcrete Ltd | Reg no. 08079452 VAT no. 194306207

Structural Waterproofing | Gas Protection  
| Concrete Repair Technical Grouts | Joint  
Sealants | Protective Coatings | Admixtures

[www.premcrete.com](http://www.premcrete.com) | 02380 276166 |  
[sales@premcrete.com](mailto:sales@premcrete.com) | 44 Macadam Way,  
West Portway, Andover, Hampshire, SP10  
3XW

The information provided in this data sheet is intended for general guidance only and is given in good faith based on Premcrete Ltd current knowledge and experience. No warranty in respect of fitness for a purpose, or any other liability whatsoever can be inferred from the information contained within this datasheet. Users should determine the suitability of the materials for their particular application and should always refer to the most recent issue of the product data sheet for the product concerned. All materials are supplied in accordance with Premcrete Ltd Sales Terms & Conditions (available upon request and on Company Website).