

EXAFOAM

Closed-Cell Polyethylene Fillerboard

DESCRIPTION

EXOFOAM is a closed cell polyethylene foam fillerboard for use in expansion joints in concrete. Its closed cell structure makes the product non-absorbent and easily compressed.

USES

EXAFOAM is a compressible joint filler board, used as a joint filler in masonry and concrete structures to provide a back of the joint sealant.

ADVANTAGES

- Excellent compressibility.
- Closed cell structure prevents water absorption.
- Easily cut to shape.

Property	Value
Elongation @ Break	Black and Grey
Tensile Strength	480 CPS @ 20°C
Recovery from Compression	40 minutes @ 20°C 100 minutes @ 10°C

PROCEDURE

Application: EXAFOAM is typically bonded to an existing structure or previously poured concrete slab using a suitable contact adhesive. If the joint is to be sealed using a joint sealant then a plastic strip joint former should be placed on top of the EXAFOAM which is removed once the concrete is poured to form a rebate for the sealant to fill.

PACKAGING & COVERAGE

EXOFOAM is supplied in 1m x 2m sheets at the following thicknesses, 10mm, 15mm, 20mm, 25mm and 30mm.

STORAGE & SHELF LIFE

EXOFOAM should be stored in clean dry conditions away from direct sunlight.

HEALTH & SAFETY

See separate material safety datasheet.

