

PREFLEX POROUS PRIMER

ONE-PART POROUS PRIMER

DESCRIPTION

PREFLEX POROUS PRIMER is a one part, solvent based, air drying isocyanate resin-based primer.

USES

PREFLEX POROUS PRIMER is for use in conjunction with PREFLEX PU and PREFLEX 300 sealants for the priming for porous substrates such as concrete, blockwork and brickwork.

Property	Value
Colour	Clear
Density	Approx. 1.0g/cm ³
Application	+5°C to 30°C

PROCEDURE

Surface Preparation: The joint surfaces must be clean, dry, and free from all contamination. Apply one coat of PREFLEX POROUS PRIMER using a clean dry brush and allow it to dry for at least 1 hour but not more than 8 hours before applying the sealant. All joint preparation and priming should be carried out in accordance with BS 8000 Part 16.

PACKAGING & COVERAGE

Pack Size: PREFLEX POROUS PRIMER is supplied in 500ml and 5 litre containers.

Coverage: Yield approximately 125 metres per 500ml, 1250 metres per 5 litres.

STORAGE & SHELF LIFE

PREFLEX POROUS PRIMER can be stored for up to 9 months in original unopened packaging, when stored in a cool, dry place and out of direct sunlight.

HEALTH & SAFETY

See separate material safety datasheet