

PREMSTRIKE 500S

Mould Release Oil

DESCRIPTION

PREMSTRIKE 500S is a special formulation consisting of a blend of mineral oils and additives which is applied to concrete formwork to give optimum release and quality of concrete.

USES

PREMSTRIKE 500S is used as a mould release agent to facilitate formwork removal and produce a concrete which is smooth hard and with a uniform finish.

ADVANTAGES

- Produces uniform stain-free quality concrete.
- Un-affected by rain.
- High coverage.

Property	Value
Appearance	Amber Liquid
Specific Gravity	0.85 @ 20°C
Flash Point	62°C

PROCEDURE

Surface Preparation: Formwork should be clean dry and free from oil, grease, and other deleterious materials. The formwork should have a consistent finish and be free from defects.

Application: PREMSTRIKE 500S should be applied to the formwork at a rate of 0.03ltrs per m². It should be applied using a suitable sprayer, such as a Gloria 172RT with an 8001 tip size. Concrete placement may commence after 4hrs.

Equipment Cleaning: Tools and equipment should be cleaned immediately using PREMCRETE CLEANING SOLVENT.

PACKAGING & COVERAGE

Pack Size: PREMSTRIKE 500S is supplied in 25ltr and 210ltr drums.

Coverage: A 25ltr drum is sufficient to cover approximately 750M².

STORAGE & SHELF LIFE

PREMSTRIKE 500S should be stored in clean dry conditions in well ventilated areas, when stored in unopened containers the product will have a shelf life in excess of 2 years.

HEALTH & SAFETY

See separate material safety datasheet.